

ATTENTION: Always refer to the **Technical Manual for Interior Flooring Products** and corresponding **Technical Data Sheets** for complete installation information prior to starting the job. Lonseal reserves the right to change our products' design, material, and/or to improve products or processes at any time without notice. Installation procedures and use of Lonseal adhesives must be in strict accordance with Lonseal's technical documents for warranty terms to be valid. Please review the website for the most current technical information.

DISCLAIMER: Please be advised that the following suggestions result from research into finding alternate products possessing properties closest to Lonseal's adhesives, or are compatible with Lonseal flooring. **These items are not covered by Lonseal's warranty**, and the responsibility of use lies with the purchaser/user. Any warranty for the chosen adhesive will be per the adhesive manufacturer. Contact the chosen manufacturer to confirm suitability for use with sheet vinyl flooring.

These items are widely available in domestic and foreign markets.

CONTACT ADHESIVE

- ▶ No equal

EPOXY ADHESIVE:

- ▶ Armstrong
 - ▷ S-240 High Performance Epoxy Flooring Adhesive
- ▶ Henry
 - ▷ 452 General Purpose Epoxy Flooring Adhesive
- ▶ Mapei
 - ▷ Ultrabond G15
- ▶ Taylor
 - ▷ EnviroPoxy #501

SHEET VINYL ADHESIVE

- ▶ Henry
 - ▷ 622 VinylBond Premium High Strength Vinyl Flooring Adhesive
- ▶ Mapei
 - ▷ Ultrabond ECO 350
 - ▷ Ultrabond ECO 360
- ▶ Taylor
 - ▷ Meta-Tec 2090
 - ▷ Meta-Tec 2091 TuffGrip

SEAM SEALER

- ▶ Armstrong
 - ▷ S-761 Seam Adhesive
- ▶ Congoleum
 - ▷ SU106 Seam Sealer
- ▶ Mannington
 - ▷ MLG33 Urethane Sealer
- ▶ Toli
 - ▷ Cold Weld Seam Sealer

OTHER ADHESIVES

- ▶ Aquaflex Waterproof Flooring Adhesive
 - ▷ For use on concrete with high moisture as an alternative to applying a moisture mitigation system and Lonseal adhesive. Visit www.formulators.com or contact Benny Dickens at (800) 359-3201 for more information.
- ▶ Spray-Lock 3100 Sheet Goods Spray Adhesive
 - ▷ Approved for use by Spray-Lock with Lonseal flooring. Visit www.spraylock.com or contact Larry Moore at (479) 631-0148 for more information.